

B SERIES



- Ultra-compact and light weight design
- Bi-Amplified design for maximum efficiency
- Balanced XLR & Jack Input.
- Convenient Line output to link with additional speakers.
- Built-in soft clip limiter to avoid distortion
- Integrated Stand mounting socket
- Ergonomically shaped handle for easy carrying and setup

B 400U (additional Features)

- 2 x mic / line (switchable) with individual level control.
- 1x USB input with remote with level control.
- 3-band Equalizer.

Technical Specifications	B 200	B 400	B 400U
Type	Active Speaker	Active Speaker	Active Speaker
Power Output (RMS / Peak) Watts	160 / 320	275 / 550	275 / 550
Frequency Response (Hz)	65-18000	60 - 18000	60 - 18000
Max SPL (dB)	118	125	125
LF Driver Size	12" Woofer	12" Woofer	12" Woofer
HF Driver Size	1"	1"	1"
Input Connector	XLR / Jack	XLR / Jack	Combo XLR / Jack
Output Connector	Jack	Jack	XLR / Jack
Dimension (WxDxH)mm /Net Weight (Kgs.)	400 x 345 x 600 /15.5	400 x 345 x 600/16.5	400 x 345 x 600/16.5
Colour	Black	Black & White	Black