

DIAMOND CLUB SERIES

The best selling & the most trusted mixing consoles in India. These mixers are built to match international standards, they are ideal for professionals as well as amateurs.

Elegant Curved Front, Attractive Grey Panel Artwork, Blue Power ON LED.



Models Available:

- DC 6.2 - 6 Mic/Line
- DC 8.2 - 8 Mic/Line
- DC 12.2 - 12 Mic/Line
- DC 16.2 - 16 Mic/Line
- DC 12.2USB (12 Mic/ Line, USB input for USB MP3 music player with remote.)
- Balanced Mic/Line Inputs
- Gain control with 3 Band EQ per channel.
- 2 Aux Sends/ Returns.
- 1 pre & 1 post aux sends rotary control per channel.
- L/R Pan Pot ,Illuminated Mute Switch & Clip LED per Channel.
- Stereo Tape in/tape out, Headphone out.
- Blue Power on LED
- 12 segments L/R LED meter for Master Level.
- ¼ TRS, L/R Main Output.
- Elegant Shape – Curve front
- Stylish Grey panel

DIAMOND CLUB SERIES WITH EFX



Models Available:

- DC 8.2 EFX - 8 Mic / Line Inputs + EFX
- DC 12.2 EFX - 12 Mic / Line Inputs + EFX
- DC 16.2 EFX - 16 Mic / Line Inputs + EFX

Additional Features:

- **Built-In Delay EFX with 3 Delay Modes, Feedback & Delay Controls.**
- Delay time ranging from 30m sec to 640m sec & unique E-delay.

Technical Specifications	DC 6.2	DC 8.2	DC 8.2 EFX	DC 12.2	DC 12.2 EFX	DC 12.2 U	DC 16.2	DC 16.2 EFX
Nominal Gain (Mic/Line)	60dB/40dB							
Max Gain (Mic/Line)	60dB/40dB							
Input Levels Sensitivity	76dB/56dB							
Mic (Gain Min/Gain Max)								
Line (Gain Min /Gain Max)	-12dBu / -60dBu							
Input impedance	+8dBu / -40dBu							
Mic Input	Typically 5K Ω balanced							
Line input	20KΩ (Balanced) /10KΩ (Unbalanced)							
Main Output level (Nominal /Max)	0dBu (0.775V RMS) / +17dBu (5.5V RMS)							
Main Output Impedance	<50Ω							
Frequency Response	25Hz to 19KHz (+0/-1 dB)							
Total Harmonic Distortion	Better than 0.8%							
Signal to Noise Ratio	-76 dB							
Clip indication	4 dB prior to true clip							
Equalisation (Treble/Mid/Bass)	±16dB @ 10KHz/2.5KHz/100 Hz							
EFX & USB	-	-	EFX	-	EFX	USB	-	EFX
Power supply	150V~250V AC/50Hz							
Dimensions (W x D x H in mm)	335x376x89	395x376x89	435x376x89	515x376x89	555x376x89	555x376x89	635x376x89	675x376x89
Net Weight (Kgs.)	3.75	4.5	4.8	5.7	6.2	6.2	6.8	7.3