

FIRE SERIES Passive Speaker



Features:

- Professional Loudspeakers systems highly recommended for a variety high quality outdoor& indoor sound reinforcement systems.
- **Attractive Brown Paint Finish enclosures.**
- Ergonomically shaped handles for easy transportation
- Dual-Speakon connectors allow linking of additional loudspeakers.
- Heavy-Gauge perforated metal speaker grille for optimal speaker protection.
- Exceptional sound quality, wide frequency bandwidth and dynamic range
- Fire 55 features unique back firing ports to enhance the bass response.
- Overload protection circuitry in mid-hi tops ensures optimal HF driver protection

| Technical Specifications | FIRE 51 | FIRE 51A | FIRE 55 | FIRE 84 |
|---------------------------------|----------------------------------|----------------------------------|--------------------------------------|--------------------------------------|
| Type | 2-Way Speaker | 2-Way Active Speaker | 2-Way Speaker | Sub-Woofer |
| Power Output (RMS / Peak) Watts | 500 / 1000 | 500 / 1000 | 950 / 1900 | 2000 / 4000 |
| Frequency Response (Hz) | 40 - 20000 | 50 - 20000 | 30 - 20000 | 30 - 2000 |
| Impedance (O) | 8 | - | 4 | 4 |
| Sensitivity (1w @1m) dB | 98 | 98 | 97 | 99 |
| Max SPL (dB) | 131 | 130 | 132 | 134 |
| LF Driver Size | 15" Woofer with 4" Voice coil | 15" Woofer with 4" Voice coil | 2 x 15" Woofer with 4" Voice coil | 2 x 18" Woofer with 4" Voice coil |
| HF Driver Size | 1" Driver | 1" Driver | 1" Throat with 1.75" coil | - |
| Input Connector | 2 x Speakon | Combo Jack | 2 x Speakon | 2 x Speakon |
| Dimension (WxDxH)mm | 450 x 408 x 690 | 450 x 408 x 690 | 450 x 530 x 1160 | 960 x 600 x 540 |
| Net Weight (Kgs.) | 33 | 35.5 | 57 | 58.1 |

FIRE 51A (Amplifier Section)

- **Driven by P-Series amplifier technology.**
- 3-Band EQ.
- 2 Mic/Line (Switchable)
- Line out (XLR / Jack)