

OP SERIES

Back Panel OP 415U



- Excellent Sound Clarity & Punch • Ultra-compact and light weight design
- Bi-Amplified design for maximum efficiency
- Balanced Combo XLR & Jack Input
- Convenient Line output to link with additional speakers
- Built-in soft clip limiter to avoid distortion
- Integrated Stand mounting socket
- Ergonomically shaped handle for easy carrying and setup

Additional Features in OP 415U & OP 515

- 2 x mic/line (switchable) with individual level control.
- 3-band Equalizer.
- 1 USB Input with remote with level control. (only in OP415U)

Technical Specifications	OP 215	OP 415	OP 415U	OP 515
Type	Active Speaker	Active Speaker	Active Speaker	Active Speaker
Power Output (RMS / Peak) Watts	160 / 320	275 / 550	275 / 550	400 / 800
Frequency Response (Hz)	50 - 20000	50 - 20000	50 - 20000	34 - 20000
Max SPL (dB)	123	127	127	130
LF Driver Size	15" Woofer	15" Woofer	15" Woofer	15" Woofer
HF Driver Size	1"	1"	1"	1"
Input Connector	Combo XLR / Jack			
Output Connector	XLR	XLR	XLR/Jack	XLR/Jack
Dimension (WxDxH) mm	440 x 320 x 700			
Net Weight (Kgs.)	16	20	20	22